



Two Remote and One Local Temperature Sensors and 3/4 Fan Controllers with SMBus Interface

Features

- Measures Two Remote and One Local Temperatures
- Adjustable Offset for Each Sensor via SMBus
- Accuracy: Remote $\pm 1^{\circ}\text{C}$ ($+20^{\circ}\text{C}$ to $+80^{\circ}\text{C}$)
 $\pm 3^{\circ}\text{C}$ (-10°C to $+120^{\circ}\text{C}$)
- +4.5V to +5.5V Supply Range
- Alert Signal for Diode Fault, Fan Fail, and Fan Out of Control
- Supports SMBus Alert Response
- Fan Drivers Using Linear Control Algorithm
- Closed Loop Speed Control and programmable 8 Bits Open Loop Voltage Control for Fan
- Wide speed control range for Fan, Accuracy within 2%, when $\text{FANx_SET_CNT} > 50$
- Internal Current-limit and Over-temperature Protection for the Fan Controllers
- Build-In Inverters for Driving Crystal
- 20-Pin TSSOP Package

Applications

- Projector, LCD TV, PDP TV
- Desktop and Notebook
- Central Office Computers
- Telecom Equipments
- Industrial Controls
- LAN Servers

General Description

The G793/G794 contains 3 precise digital thermometers, 3/4 fan controllers, fan failure detection.

The thermometers report the temperature of 2 remote sensors and 1 local sensor. The remote sensors are diode-connected transistors typically a low-cost, easily mounted 2N3904 NPN type or the diode built-in in CPU. Remote accuracy is $\pm 1^{\circ}\text{C}$ for multiple transistor manufacturer. Local accuracy is $\pm 3^{\circ}\text{C}$. The G793/G794 also support offset adjust function via SMBus to fix the error due to different CPU diode or parasitic resistors.

The 2-wire serial interface accepts standard System Management Bus (SMBus™) Write Byte, Read Byte, Send Byte, and Receive Byte commands. The SMBus address is 72h for write and 73h for read.

G793/G794 contains 3/4 controllers. FAN controller performs closed-loop and open-loop control. G793/G794 determines the current fan speed based on the FG inputs and an externally supplied 32.768kHz clock. The driving ability is 5mA. G793/G794 also provides ALERT for fan fail and out of control event.

SMBus™ is a trademark of Intel Corp

Ordering Information

ORDER NUMBER	MARKING	TEMP. RANGE	PACKAGE (Green)
G793D5U	G793	-55°C to +125°C	TSSOP-20
G794D5U	G794	-55°C to +125°C	TSSOP-20

Note: D5: TSSOP-20

U: Tape & Reel

GMT Inc. does not assume any responsibility for use of any circuitry described, no circuit patent licenses are implied and GMT Inc. reserves the right at any time without notice to change said circuitry and specifications.

Pin Configuration

